

FLOOR SEALER PRO-SEAL

Pure Acrylic Sealer & Undercoater



DESCRIPTION

A hard, clear, brilliant primer that keeps water, dirt, and abrasive wear from penetrating into floors. Gives longer lasting protection, stays clear and eliminates frequent stripping thereby saving costs on maintenance. Minimizes heel marking and scuffing. Ideal as a base coat for all floor finishes. Use on concrete, terrazzo, and all resilient floors such as vinyl, rubber, vinyl composition, asphalt, linoleum.

PRODUCT FEATURES / BENEFITS

- Superior surface protection / Extends life of wear surface for maximum optimal appearance
- No etching required / Reduces labor costs in application
- Multi-polymer emulsion / Provides for optimum gloss, durability and chemical resistance
- High solids formula / Maximum wear surface available to eliminate re-coating
- Water-based emulsion / No toxic fumes, fire hazards or lengthy drying times

DIRECTIONS FOR USE

Floor Preparation: Strip floor thoroughly with a preferred floor stripper, making sure that all old film is removed. Rinse completely and allow to dry. Application of Sealer: Using a clean string mop or applicator, apply a thin even coat of PRO-SEAL and allow to dry for at least 30 minutes. On very porous floors apply a thick coat and allow to soak to 5 minutes. Pick up excess, if any, before PRO-SEAL begins to dry. To increase the evenness of appearance of the surface a second coat may be applied. After PRO-SEAL has been allowed to completely cure, apply the recommended floor finish following recommendations on product label.

SPECIFICATIONS

Flow	Excellent	Nonslip	Yes
Leveling	Excellent	Flash Point	None
Durability	Excellent	Odor	Mild Acrylic
Transparency	Water Clear	Polymer Type	Multiple Component
Chemical Resistance	Superior	Resin Type	Thermoplastic
Gloss 60°	91	Freeze-Thaw	Protect from Freezing
Flexibility	Excellent	Specific Gravity (g/cc).....	1.01 ± 0.01
Emulsion pH	8.1 ± 0.3	Density (lbs/gal).....	8.5 ± 0.1
Coverage	1st coat 600-800 sq.ft./gal	Removable	Yes with special stripper
.....	2nd coat 1200-1600 sq.ft./gal	Shelf Life	1 year minimum in original unopened container
Viscosity (cps)	7 to 10		

SAFETY INFORMATION

KEEP OUT OF REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash hands after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures: Read the entire label and SDS before using this product, and for additional first aid measures.

KEEP FROM FREEZING

FOR SALE TO, USE AND STORAGE BY SERVICE PERSONNEL ONLY